

PRODUCT DESCRIPTION

A 3 mil LDPE product for general surface protection on mill finishes, such as standard steel polishers grade, during fabrication and/or shipping. The custom formulated acrylic adhesive offers a "medium adhesion" product with minimal adhesion build.

SUGGESTED END USE

Smooth and Matte Polycarbonate, Medium Polish Stainless Steel, Smooth Formica, Anodized Aluminum, Mill Finish Aluminum, Painted Metals

FEATURES

Removable

Conformable

Easy Application

BENEFITS

Clean, stain free removal... even after application for extended time periods.

Product remains intact... even after extreme bending.

The controlled unwind allows for application using either manual or automatic methods.

PRODUCT SPECIFICATIONS

Total thickness	2.7 mils
Tensile strength	6 lbs/inch
Elongation	325%
Standard roll width (inches)	36", 48", 60"
Standard roll length (yards)	200, 334, 500, 1000
Backing	LDPE
Adhesive type	Acrylic
Color	Clear, White or Blue
Adhesion, pstc 1	6 oz/inch

The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for their intended use under their own operating conditions. Protective Packaging assumes no liability for claims beyond the replacement value of any defective products, and is in no way liable for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.