

PRODUCT DESCRIPTION

Protective Film 2A26 is a co-extruded, medium adhesion protective film designed for a variety of surface protection applications

SPECIFICATIONS

| | |
|--------------------|--------------------------------|
| Colours: | Clear |
| Nominal Thickness: | 2.0 mils (0.05mm) |
| Adhesion: | 9 oz./in. width (2.5 N/25 mm) |
| Tensile Strength: | 4500 PSI |
| Elongation: | 600% |

PERFORMANCE FEATURES

Surface protection against dust, dirt, scratches, and abrasion encountered in processing, handling, shipping and storage. Stable adhesion levels resulting in good removability. 2A26 proprietary high-performance film with higher abrasion resistance vs. many typical thicker gauge films, offering good clarity, excellent conformability for hand and machine applications. Increased break strength for easier removability without tearing or slivering.

RECOMMENDED END APPLICATIONS

General – smooth semi-gloss cultured marble, high pressure laminates. Metals – 2B and #3 finish stainless steel. Painted – smooth satin-gloss. Painted – lightly textured semi/high-gloss. Plastics – smooth satin-gloss. Plastics - lightly textured semi/high-gloss

DISCLAIMER

The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their intended use. Protective Packaging assumes no liability for claims beyond the replacement value of our product proved to be defective.