

PRODUCT DESCRIPTION

Protective Film 25AU76B/UV is a co-extruded, high adhesion protective film. Features UV resistance of up to 3 months for temporary surface protection.

SPECIFICATIONS

Colours:	Blue
Adhesion:	12oz./in. width (3.3 N/25 mm)
Tensile Strength:	4500 PSI
Elongation:	600%

PERFORMANCE FEATURES

UV resistant film backing and non-corrosive, acrylic adhesive for stable performance and clean. Removal based on short term accelerated lab testing data. It is strongly recommended that user evaluate UV performance on actual substrate under conditions of use. 25AU76 proprietary high-performance film with higher abrasion resistance vs. many typical thicker gauge films, offering excellent conformability for hand and machine applied applications. Increased break strength for easier removability without tearing or slivering.

RECOMMENDED END APPLICATIONS

General – smooth flat-gloss cultured marble, high pressure laminates. **Painted** - smooth flat-gloss. **Painted** – lightly/medium textured flat/satin-gloss. **Plastics** - smooth flat-gloss. **Plastics** – lightly/medium textured flat/satin-gloss

DISCLAIMER

The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their intended use. Protective Packaging assumes no liability for claims beyond the replacement value of our product proved to be defective.