

PRODUCT DESCRIPTION

This is a temporary masking product designed to protect synthetic carpets from tracked in dirt, spills, dust, and damage during high traffic conditions. The Polyethylene film is a special blend which is resistant to tears and punctures from sharp items such as tools or high heels. The acrylic adhesive system allows for clean removal. This product should not be used in high humidity conditions or in outdoor applications.

SPECIFICATIONS

| | |
|--------------------|-------------|
| Colours: | Clear |
| Nominal Thickness: | 2 mils |
| Tack Level: | High |
| Tensile Strength: | 11 lb/sq in |
| Elongation: | 630% |

PERFORMANCE FEATURES

The Polyethylene film is a special blend which is resistant to tears and punctures from sharp items such as tools or high heels. The acrylic adhesive system allows for clean removal. This product should not be used in high humidity conditions or in outdoor applications.

RECOMMENDED END APPLICATIONS

This is a temporary masking product designed to protect synthetic carpets from tracked in dirt, spills, dust, and damage during high traffic conditions.

DISCLAIMER

The physical properties listed above are typical values and are not to be construed as specifications. Our suggestions and recommendations for use are based on tests we believe to be reliable. However, the purchaser must determine the suitability of the product for their intended use. Protective Packaging assumes no liability for claims beyond the replacement value of our product proved to be defective.